

## STOCK RANGE

g/m <sup>2</sup>	450 x 620	450 x 640	520 x 720	630 x 880	640 x 900	880 x 630	720 x 1020
80		✓		✓	✓		✓
90		✓	✓	✓	✓	✓	✓
100		✓	✓	✓	✓	✓	✓
105		✓		✓	✓		✓
115		✓	✓	✓	✓	✓	✓
118		✓	✓	✓	✓		✓
128		✓	✓	✓	✓	✓	✓
140		✓	✓	✓	✓	✓	✓
148	✓	✓	✓	✓	✓	✓	✓
157		✓	✓	✓	✓		✓
170		✓	✓	✓	✓		✓
200		✓	✓	✓	✓		✓
250		✓	✓	✓	✓		✓
300		✓	✓	✓	✓		✓
330		✓			✓		✓

## SUSTAINABILITY

Carbon  
Balanced

PEFC



ECF


ISO  
9001ISO  
14001ISO  
45001

## TECHNICAL SPECIFICATIONS

Weight	Thickness	Gloss	Brightness	Opacity
g/m <sup>2</sup>	µm	%	%	%
80	72	35	90	90
90	78	35	90	92
100	91	35	90	94
105	95	30	90	94
115	106	30	90	95
118	111	30	90	94
128	118	30	90	96
140	134	30	89.5	98
148	146	30	89	98
157	153	30	89.5	98.5
170	168	30	89.5	98.5
200	200	30	89.5	98.5
250	250	30	89.5	98.5
300	283	30	89.5	98.5
330	320	30	89.5	98.5

denmaur 

www.denmaur.com

CALISTO  
SILK