

Eurotak

A range of high quality self-adhesive papers

- Made from FSC® certified pulp sources
- Sourced from one of the leading label manufacturers in Europe
- Stocked in a range of options for next day delivery
- Manufactured in accordance with ISO certified standards for environmental, quality and energy management

Eurotak Vellum Face (uncoated)			
Face Material		Liner	
Substance	75g/m ²	Substance	90g/m ²
Thickness	70µm	Thickness	90µm
Brightness	101.5 ISO	Tensile strength kN/m	5.2/2.6
Whiteness	158.2% CIE		
Opacity	89 ISO		

Eurotak Gloss Face			
Face Material		Liner	
Substance	80g/m ²	Substance	90g/m ²
Thickness	67µm	Thickness	90µm
Brightness	93 ISO	Tensile strength kN/m	5.2/2.6
Whiteness	117% CIE		
Opacity	88.5 ISO		
Gloss 75°	66 ISO		

Stock Range		
Eurotak Vellum Face (uncoated)		
	450x640	500x700
Solid/Perm	✓	✓
Split/Perm	✓	
Eurotak Gloss Face		
	450x640	500x700
Solid/Perm	✓	✓
Split/Perm	✓	✓
Split/Remove		✓









Adhesive: Removable		
Adhesion	N/25min	1.7
Tack	N	1.2
Shear	min	120
Min labelling temp	°C	+5
Min service temp	°C	-20
Max service temp	°C	+80

Adhesive: Permanent		
Adhesion	N/25min	15.4
Tack	N	10.3
Shear	min	100
Min labelling temp	°C	+5
Min service temp	°C	-20
Max service temp	°C	+80

Eurotak Laser Digi			
Face Material		Liner	
Substance	70g/m ²	Substance	90g/m ²
Thickness	90µm	Thickness	90µm
Brightness	103 ISO	Tensile strength kN/m	5.2/2.6
Whiteness	143 % CIE		
Opacity	91 ISO		

Eurotak Digi Gloss Face			
Face Material		Liner	
Substance	80g/m ²	Substance	90g/m ²
Thickness	67µm	Thickness	90µm
Brightness	93 ISO	Tensile strength kN/m	5.2/2.6
Whiteness	117% CIE		
Opacity	88.5 ISO		
Gloss 75°	66 ISO		

Stock Range	
Eurotak Laser Digi	
	320x450
Solid/Perm	✓
Split/Perm	✓
Eurotak Gloss Digi	
	320x450
Solid/Perm	✓
Split/Perm	✓

			
FSC®	Carbon Balanced OPTION	ISO 9001	ISO 14001
			
ISO 45001	ISO 50001	EMAS	REACH