



**Laser guaranteed luxury
preprint offset**

**Excellent dimensional stability and fast drying times
combined with super smooth surface and high
brightness**

KEY FEATURES & BENEFITS

- 70-350gsm
- Laser suitable pre-print offset
- 98.5% brightness
- Excellent colour reproduction
- Exceptional bulk and opacity
- Fast ink setting
- PEFC certified

SPECIFICATIONS

	Unit	Standards	Specification														
			70	80	90	100	110	120	140	160	170	180	200	210	250	300	350
Basis Weight	g/m ²	T410 om-98	70	80	90	100	110	120	140	160	170	180	200	210	250	300	350
Thickness	µm	T411 om-97	90±4	100±4	112±4	125±5	138±5	151±5	174±5	190±5	203±5	215±5	233±5	245±6	278±6	340±7	370~385
Smoothness	sec/10ml	T479 om-91	47±10	47±10	47±10	45±10	45±10	45±10	45±10	45±10	45±10	45±10	45±10	45±10	45±10	40±10	38±10
Brightness	%ISO (C/2°)	ISO 2470-1999	98.5±1	98.5±1	98.5±1	98.5±1	98.5±1	98.5±1	98.5±1	98.5±1	98.5±1	98.5±1	98.5±1	98.5±1	98.5±1	98.5±1	98.5±1
Opacity	%	ISO 2471-1999	≥90	≥92	≥93	≥95	≥96	≥97	≥98	≥99	≥99	≥99	≥99	≥99	≥99	≥99	≥99

KEY APPLICATIONS



Diaries



Direct Mail /
Envelope
Production



Inserts



Manuals



Maps



Menus



Notebooks &
Pads