DeliPac

heat-sealable | biodegradable™

STOCK RANGE	
g/m² / mic	720 x 1020
240/350	•
270/410	•
315/500	•

TECHNICAL SPECIFICATIONS					
Weight	Thickness	Brightness	Taber MD	Taber CD	Gloss
g/m²	ISO 534 µm	ISO 2470 %	(gf/cm)	(m/mn)	Hunter %
215	305	90	8.4	4.5	53
240	350	90	12.1	6.5	53
255	380	90	14.9	8.5	53
265	400	90	15.5	9.1	53
270	410	90	17.6	9.9	53
285	450	90	22	12.1	53
315	500	90	27.5	14.9	53
335	550	90	33.5	17.6	53
370	600	90	38.5	22.6	53

DeliPac

PRINT PROCESSES	
Litho	Digital*
✓	✓

* Compatible with a number of digital presses, please contact your local sales office for further information

FINISHING SUITABILITY							
Laminate	Spot UV	Varnish	Foil Block	Folding	Die Cut	Embossing	Scoring
✓	✓	✓	✓	✓	✓	✓	✓

SUSTAINABILITY STATEMENT				
PULP		ENVIRONMENTAL	QUALITY	ENERGY
PEFC	ECF	ISO 14001	ISO 9001	ISO 50001
✓	✓	✓	✓	✓

PRODUCT COMPLIANCE		
Modern Slavery Act	✓	Supply chain for this product has been fully risk assessed
Pulp Traceability	✓	Full details available on request
Product Safety	✓	Certificate available on request

Updated – 18th April 2019