



revive™ Media Plus Matt

TECHNICAL SPECIFICATIONS

	Strength	Gloss	Brightness	Opacity	FSC	Carbon
GSM	ISO 1924-2 km	ISO 8254-1 %	ISO 2470 %	DIN 53146 %	Recycled	Balanced
60*	5,0	≤30	79	≥94	100%	✓
65*	5,0	≤30	79	≥94	100%	✓
70*	5,0	≤30	81	≥96	100%	✓
80*	5,0	≤30	81	≥96	100%	✓
90*	5,0	≤30	83	≥98	100%	✓
100*	5,0	≤30	83	≥98	100%	✓
115*	5,0	≤30	83	≥98	100%	✓

* Please note that these weights are available from the mill

FINISHING SUITABILITY

Laminate	Varnish	Foil Block	Folding	Die Cut	Embossing	Scoring
✓	✓	✓	✓	✓	✓	✓

PRINTING PROCESSES

Litho	HSWO*	CutStar	Gravure
✓	✓	✓	✓

* equivalent available on order

SUSTAINABILITY STATEMENT

PULP		ENVIRONMENTAL				QUALITY	ENERGY	H&S
PEFC™	FSC®	EU EcoLabel	Blue Angel	EMAS	ISO 14001	ISO 9001	ISO 50001	ISO 45001
✓	✓	✓	✓	✓		✓	✓	✓

FSC® Forest Stewardship Council forest management certification scheme
 Blue Angel The ecolabel of the Federal Government of Germany since 1978
 ISO14001 International standard for environmental management
 EMAS Eco-Management and Audit Scheme

ISO9001 International standard for quality management
 ISO50001 International standard for energy management
 ISO45001 International standard for health & safety management

Please note that this product is ex-mill only.
 Please contact your local Denmaur office for further information.

Updated 06/04/23